

Page 1/8

GB

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 24.11.2020

Version: 1.1

Revision: 24.11.2020



Printing date 24.11.2020

Revision: 24.11.2020

	(Contd. of page 1)
Hazard statements	
H225 Highly flammable liquid and vapour.	
H336 May cause drowsiness or dizziness.	
H412 Harmful to aquatic life with long lasting effects.	
Precautionary statements	
P101 If medical advice is needed, have product container or label at hand.	
P102 Keep out of reach of children.	
P271 Use only outdoors or in a well-ventilated area.	
<i>P501 Dispose of contents/container to hazardous waste collection point.</i>	
Additional information:	
EUH066 Repeated exposure may cause skin dryness or cracking.	
2.3 Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:			
EC/List number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	30-50%	
Reg.nr.: 01-2119463258-33	aromatics		
	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; ۯ STOT SE 3, H336		
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	10-20%	
EINECS: 265-151-9 Reg.nr.: 01-2119473851-33	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336		
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	10-20%	
EC/List number: 918-668-5 Reg.nr.: 01-2119455851-35	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336		
CAS: 67-63-0	propan-2-ol	1-2.5%	
EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336		
• Additional information: For	the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

• Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents: Water spray

 \cdot 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases/vapours is possible during heating or in case of fire.

(Contd. on page 3)

GB

Printing date 24.11.2020

Revision: 24.11.2020

(Contd. of page 2)

GB

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. • 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect from heat. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- *Further information about storage conditions:* Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

· Storage class: -

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol (1-2.5%) WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

· DNELs

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

	, , , , , , , , , , , , , , , , , , ,			
Oral	DNEL, long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)		
Dermal	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)		
		208 mg/kg bw/day (Employee)		
Inhalative	DNEL,long term (chronic) - systemic effects	185 mg/m3 (Consumer)		
		871 mg/m3 (Employee)		
64742-95-6 Hydrocarbons, C9, aromatics				
Oral	DNEL, long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)		
Dermal	DNEL,long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)		
		(Contd. on page 4)		

Printing date 24.11.2020

Revision: 24.11.2020

Inhalative	DNEL,long term (c	hronic) - systemic effects	(Contd. of page) 25 mg/kg bw/day (Employee) 32 mg/m3 (Consumer)
		/ 2 00	150 mg/m3 (Employee)
67-63-0 pr	opan-2-ol		
Oral	DNEL,long term (c	hronic) - systemic effects	26 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	hronic) - systemic effects	319 mg/kg bw/day (Consumer)
			888 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	
			500 mg/m3 (Employee)
PNECs			
67-63-0 pr	-		
PNEC, fresh		140.9 mg/l (aquatic orgo	
PNEC,mar		140.9 mg/l (aquatic orgo	
		552 mg/kg (aquatic orga	
		552 mg/kg (aquatic orga	
PNEC,soil		28 mg/kg (terrestrial org	(anism)
Protection	oj nanas.		
IM		eated contact is likelv. ch	emicalresistant gloves are recommended.
	If prolonged or rep		emicalresistant gloves are recommended.
Material of Penetration The exact of observed.	If prolonged or rep f gloves Nitrile rubl n time of glove mat break trough time l	ber, NBR f erial	emicalresistant gloves are recommended. e manufacturer of the protective gloves and has to
Material of Penetration The exact is observed. Eye protect	If prolonged or rep f gloves Nitrile rubl n time of glove mat break trough time l	ber, NBR e rial has to be found out by th	
Material of Penetration The exact of observed. Eye protect	If prolonged or rep f gloves Nitrile rubb n time of glove mat break trough time l tion: Safety glasses if ris. N 9: Physical at	ber, NBR erial has to be found out by th k of splashes. nd chemical properti	e manufacturer of the protective gloves and has to
Material of Penetration The exact of observed. Eye protect SECTIO 9.1 Inform General In	If prolonged or rep f gloves Nitrile rubb n time of glove mat break trough time I tion: Safety glasses if ris. N 9: Physical an ation on basic physican	ber, NBR erial has to be found out by th k of splashes.	e manufacturer of the protective gloves and has to
Material of Penetration The exact of observed. Eye protect SECTIO 9.1 Inform General In Appearance	If prolonged or rep f gloves Nitrile rubb n time of glove mat break trough time I tion: Safety glasses if ris. N 9: Physical an ation on basic physican	ber, NBR erial has to be found out by th k of splashes. nd chemical properti sical and chemical prope	e manufacturer of the protective gloves and has to
Material of Penetration The exact of observed. Eye protect SECTIO 9.1 Inform General In Appearance Form:	If prolonged or rep f gloves Nitrile rubb n time of glove mat break trough time I tion: Safety glasses if ris. N 9: Physical an ation on basic physican	ber, NBR erial has to be found out by th k of splashes. nd chemical properti sical and chemical prope Fluid	e manufacturer of the protective gloves and has to es rties
Material of Penetration The exact of observed. Eye protect SECTIO 9.1 Inform General In Appearance Form: Colour:	If prolonged or rep f gloves Nitrile rubb n time of glove mat break trough time I tion: Safety glasses if ris. N 9: Physical an ation on basic physican	ber, NBR erial has to be found out by th k of splashes. nd chemical properti sical and chemical prope Fluid	e manufacturer of the protective gloves and has to es rties product specification
Material of Penetration The exact of observed. Eye protect SECTIO 9.1 Inform General In Appearance Form:	If prolonged or rep f gloves Nitrile rubb n time of glove mat break trough time I tion: Safety glasses if ris. N 9: Physical an ation on basic physican	ber, NBR Terial has to be found out by th k of splashes. nd chemical properti sical and chemical prope Fluid According to	e manufacturer of the protective gloves and has to es rties product specification c

(Contd. on page 5) GB

Printing date 24.11.2020

Version: 1.0

Revision: 24.11.2020

	(Contd. of page
Initial boiling point and boiling range	г: 107-137 °С
Flash point:	1 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
Oxidising properties	No further relevant information available.
Vapour pressure at 20 °C:	2.1-13 hPa
Density at 20 °C:	$0.84 \ g/cm^3$
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	$>20.5 \text{ mm}^{2}/\text{s}$
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).
- · 10.3 Possibility of hazardous reactions
- Dangerous reactions are not expected if the product is handled according to its intended use.
- 10.4 Conditions to avoid Keep away from sources of ignition No smoking.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

Hydrocarb	oons, C9-C	11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
64742-49-	0 Naphtha	(petroleum), hydrotreated light
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)
64742-95-	6 Hydroca	rbons, C9, aromatics
Oral	LD50	2,000-5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
		(Contd. on page

Printing date 24.11.2020

Revision: 24.11.2020

_				
	67-63-0 pr	opan-2-ol		
	Oral	LD50	5,840 mg/kg (rat)	
	Dermal	LD50	13,900 mg/kg (rabbit)	
	Inhalative	LC50/6h	>25 mg/l (rat)	

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
 14.2 UN proper shipping name ADR IMDG, IATA 	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL	
,		(Contd. on page 7)

GB

Printing date 24.11.2020

Version: 1.0

Revision: 24.11.2020

	(Contd. o
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
3	
	2 Elanmahla lianida
Class Label	3 Flammable liquids. 3
	-
14.4 Packing group	None.
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	<i>F-E,S-<u>E</u></i>
Stowage Category	B
14.7 Transport in bulk according to Annex II o	of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
_	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 8)

Printing date 24.11.2020 Revision: 24.11.2020 (Contd. of page 7) • 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out. **SECTION 16: Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. • Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Version: 1.0



Page 1/9

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830



2015/830

Revision: 26.11.2020

(Contd. of page 1)

Printing date 26.11.2020

Version: 1.0

· Hazard statements	
---------------------	--

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- *P211* Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to hazardous waste collection point.

• Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	30-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane, pure ♦ Flam. Gas 1A, H220; ♦ Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-20%
CAS: 64742-95-6 EC/List number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	5-10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-5%
· Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After eye contact: Rinse opened eye for several minutes under running water.*
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GR

Printing date 26.11.2020

Version: 1.0

Revision: 26.11.2020

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- *Suitable extinguishing agents:* CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Keep away from ignition sources.*
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect from heat.
 Protect against electrostatic charges.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Do not seal receptacle gas tight.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- · Storage class: -
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure (10-20%)

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

GB

Printing date 26.11.2020

Revision: 26.11.2020

67-63-0 pr	opan-2-ol (2.5-5%)		(Contd. of pag
-	<i>t-term value: 1250</i>	mg/m ³ , 500 ppm	
	g-term value: 999 m		
DNELs			
Hydrocarb	oons, C9-C11, n-alk	anes, isoalkanes, cyclics,	<2% aromatics
Oral	DNEL,long term (c	hronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	hronic) - systemic effects	125 mg/kg bw/day (Consumer)
			208 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	185 mg/m3 (Consumer)
			871 mg/m3 (Employee)
64742-95-	6 Hydrocarbons, C	9, aromatics	
Oral	DNEL,long term (c	hronic) - systemic effects	11 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	hronic) - systemic effects	11 mg/kg bw/day (Consumer)
			25 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	32 mg/m3 (Consumer)
			150 mg/m3 (Employee)
67-63-0 pr	opan-2-ol		
Oral			26 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	hronic) - systemic effects	319 mg/kg bw/day (Consumer)
			888 mg/kg bw/day (Employee)
Inhalative	DNEL, long term (chronic) - systemic effects		
			500 mg/m3 (Employee)
PNECs			
67-63-0 pr	opan-2-ol		
PNEC,fres	h water	140.9 mg/l (aquatic orga	inism)
PNEC,mar	rine water	140.9 mg/l (aquatic orga	unism)
PNEC,fres	h water sediment	552 mg/kg (aquatic orga	nism)
PNEC,mar	rine water sediment	552 mg/kg (aquatic orga	nism)
PNEC,soil		28 mg/kg (terrestrial org	ranism)
8.2 Exposi	ure controls		
	protective equipmen	<i>t</i> :	
	rotective and hygien		
	[,] from foodstuffs, be ls before breaks and		
	y protection: Not re	Ũ	
Protection		<i>q c</i>	
dlb			
THE PARTY OF	If prolonged or rep	eated contact is likely, ch	emicalresistant gloves are recommended.
Material o	f gloves Nitrile rubl	per, NBR	
Penetratio	n time of glove mat	erial	
	break trough time l	as to be found out by th	e manufacturer of the protective gloves and has to
observed.			

Printing date 26.11.2020 Version: 1.0 Re

Revision: 26.11.2020

(Contd. of page 4)

• Eye protection:

Safety glasses

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
pH-value:	Not applicable.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	154-193 °C
Flash point:	-97 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
Oxidising properties	No further relevant information available.
Vapour pressure at 20 °C:	8,300 hPa
Density at 20 °C:	$0.68 \ g/cm^3$
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).

· 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

• 10.4 Conditions to avoid No further relevant information available.

 \cdot 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

GB

Printing date 26.11.2020

Revision: 26.11.2020

	(Contd. of page 5)
• 10.6 Hazardous decomposition products: No decomposition if used according to specifications	

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

Hydrocarbons, C	9-C11, n-alkanes,	isoalkanes, cyclics,	<2% aromatics
-----------------	-------------------	----------------------	---------------

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5.000 mg/kg (rabbit)

Inhalative LC50/4 h > 5,000 mg/l (rat)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

64742-9	5-6 Hydroc	arbons, C9, aromatics
Oral	LD50	2,000-5,000 mg/kg (rat)

Dermal	LD50	>2,000 mg/kg (rabbit)

67-63-0 propan-2-ol

 Oral
 LD50
 5,840 mg/kg (rat)

 Dermal
 LD50
 13,900 mg/kg (rabbit)

 Inhalative
 LC50/6h
 >25 mg/l (rat)

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity* Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Harmful to aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

GR

Printing date 26.11.2020

Revision: 26.11.2020

(Contd. of page 6)

GB

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class	2 Gases.
Label	2
Class	2.1
Label	2.1
14.4 Packing group	None.
ADR	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear of
	living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre. Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.

Printing date 26.11.2020

Version: 1.0

Revision: 26.11.2020

	(Contd. of pag
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anne	x II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P3a FLAMMABLE AEROSOLS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)

⁻ GB

Printing date 26.11.2020

Version: 1.0

Revision: 26.11.2020

(Contd. of page 8)
· Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity - inhalation – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3




Page 1/9

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 25.11.2020

Version: 1.1

Revision: 25.11.2020



		2013/030	
Printing date	25.11.2020	Version: 1.0	Revision: 25.11.2020
			(Contd. of page 1)
· Hazard-o	determining components of	of labelling:	
		isoalkanes, cyclics, <2% aromatics	
· Hazard s	statements	·	
H222-H2	229 Extremely flammable a	erosol. Pressurised container: May but	rst if heated.
H336	May cause drowsiness	or dizziness.	-
H412	Harmful to aquatic life	with long lasting effects.	
· Precauti	onary statements		
P101	If medical advice is ne	eded, have product container or label a	at hand.
P102	Keep out of reach of c	hildren.	
P210	Keep away from heat,	hot surfaces, sparks, open flames and c	other ignition sources. No smoking.
P211	Do not spray on an op	en flame or other ignition source.	
P251	Do not pierce or burn,	even after use.	
P260	Do not breathe spray.		
P271	Use only outdoors or i	n a well-ventilated area.	
P410+P4	412 Protect from sunlight.	Do not expose to temperatures exceeding	ing 50 °C/122 °F.
P501	Dispose of contents/co	ntainer to hazardous waste collection p	point.
• Addition	al information:		
		ause skin dryness or cracking.	
· 2.3 Othe	r hazards		
	of PBT and vPvB assessme	ent	
	t applicable.		
• vPvB: No	ot applicable.		

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
EC/List number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	30-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220; Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-20%
	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	5-10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-5%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

· After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness.

(Contd. on page 3)

GB

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

• *Suitable extinguishing agents:* CO2, sand, extinguishing powder. Do not use water.

• For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Information about fire - and explosion protection:
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location. Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Not required.

- Information about storage in one common storage facult • Further information about storage conditions:
- Do not seal receptacle gas tight.
- *Store in cool, dry conditions in well sealed receptacles.*
- Protect from heat and direct sunlight.

· Storage class: -

· 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 3)

-		that require monitoring a	t the workplace:
	outane, pure (10-20	· ·	
	t-term value: 1810 g-term value: 1450 i		
	c (if more than $0.1%$		
67-63-0 pr	opan-2-ol (2.5-5%)		
	t-term value: 1250 g-term value: 999 m		
DNELs			
Hydrocarb	oons, C9-C11, n-alk	anes, isoalkanes, cyclics,	<2% aromatics
Oral	DNEL,long term (c	hronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	hronic) - systemic effects	125 mg/kg bw/day (Consumer)
			208 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	Č (
			871 mg/m3 (Employee)
	6 Hydrocarbons, C	-	
Oral	e ,	, ,	11 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	chronic) - systemic effects	11 mg/kg bw/day (Consumer)
1110			25 mg/kg bw/day (Employee)
Inhalative DNEL,long term (c		nronic) - systemic effects	32 mg/m3 (Consumer) 150 mg/m3 (Employee)
67-63-0 pr	onan-2-ol		150 mg/m5 (Employee)
Oral	-	hronic) - systemic effects	26 mg/kg bw/day (Consumer)
Dermal	e ,	, ,	319 mg/kg bw/day (Consumer)
	, <u>o</u> (/ 5 55	888 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	89 mg/m3 (Consumer)
			500 mg/m3 (Employee)
PNECs			1
67-63-0 pr	opan-2-ol		
PNEC,fres	h water	140.9 mg/l (aquatic orga	inism)
PNEC,mar	ine water	140.9 mg/l (aquatic orga	unism)
-	h water sediment	552 mg/kg (aquatic orga	
		552 mg/kg (aquatic orga	nism)
PNEC,soil		28 mg/kg (terrestrial org	ranism)
Personal p General pr Keep away Wash hand	y protection: Not re	tic measures: verages and feed. I at the end of work.	

· Material of gloves Nitrile rubber, NBR

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830



· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Safety glasses

SECTION 9: Pl	hysical and	l chemical	properties

9.1 Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
pH-value:	Not applicable.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: 154-193 °C
Flash point:	-97 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air
	vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
• Oxidising properties	No further relevant information available.
Vapour pressure at 20 °C:	8,300 hPa
Density at 20 °C:	$0.68 g/cm^3$
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).
- 10.3 Possibility of hazardous reactions
- Dangerous reactions are not expected if the product is handled according to its intended use.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)

GB

 Printing date 25.11.2020
 Version: 1.0
 Revision: 25.11.2020

· 10.5 Incompatible materials: No further relevant information available.

(Contd. of page 5)

• 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	LD/LC50 values relevant for classification:		
Hydrocarb	ons, C9-C	11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>5,000 mg/l (rat)	
106-97-8 b	utane, pui	'e	
Inhalative	LC50/4 h	658 mg/l (rat)	
64742-95-6 Hydrocarbons, C9, aromatics			
Oral	LD50	2,000-5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
67-63-0 pr	opan-2-ol		
Oral	LD50	5,840 mg/kg (rat)	
Dermal	LD50	13,900 mg/kg (rabbit)	
Inhalative	LC50/6h	>25 mg/l (rat)	

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.*

• STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes: Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 6)

SECTION 13: Disposal considerations

• Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

OLS Iammable
<i>Iammable</i>
е.
ses.
d from sources of heat.
ROSOLS with a maximum capacity of 1 litr For AEROSOLS with a capacity above 1 litr For WASTE AEROSOLS: Category C, Clear s.
ROSOLS with a maximum capacity of 1 litre as for class 9. Stow "separated from" class ision 1.4.
LS with a capacity above 1 litre: s for the appropriate subdivision of class 2. EROSOLS:
s for the appropriate subdivision of class 2.
er E ivi O a A

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

	(Contd. of page
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
·IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 25.11.2020 Version: 1.0 Revision: 25.11.2020 (Contd. of page 8) CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - inhalation – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3




Page 1/9

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 25.11.2020

Version: 1.1

Revision: 25.11.2020



		2013/830	
rinting date	25.11.2020	Version: 1.0	Revision: 25.11.2020
			(Contd. of page 1)
· Hazard-a	letermining components	of labelling:	
Hydrocar	rbons, C9-C11, n-alkanes	, isoalkanes, cyclics, <2% aromatics	
· Hazard s	tatements		
H222-H2	29 Extremely flammable	aerosol. Pressurised container: May bu	rst if heated.
H336	May cause drowsines.	s or dizziness.	·
H412	Harmful to aquatic lif	e with long lasting effects.	
· Precautio	onary statements	0 0 0	
P101	If medical advice is n	eeded, have product container or label d	at hand.
P102	Keep out of reach of		
P210	Keep away from heat	hot surfaces, sparks, open flames and o	other ignition sources. No smoking.
P211		pen flame or other ignition source.	5
P251	Do not pierce or burn		
P261	Avoid breathing dust	fume/gas/mist/vapours/spray.	
P304+P3	340 IF INHALED: Remov	e person to fresh air and keep comforta	ble for breathing.
P405	Store locked up.		
P410+P4	12 Protect from sunlight	Do not expose to temperatures exceeding	ng 50 °C/122 °F.
P501	Dispose of contents regulations.	container in accordance with loca	l/regional/national/international
· Addition	al information:		
		cause skin dryness or cracking.	
· 2.3 Other	r hazards	· _	
· Results o	f PBT and vPvB assessm	ent	
	, t applicable.		
	ot applicable.		

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ∲ Flam. Liq. 3, H226; ∳ Asp. Tox. 1, H304; ∲ STOT SE 3, H336	30-50%
1	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-20%
	butane, pure ♦ Flam. Gas 1A, H220; ♦ Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-20%
EC/List number: 918-668-5	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	5-10%
1	propan-2-ol 🚸 Flam. Liq. 2, H225; ۯ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-5%
Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness.

 $(Contd. \ on \ page \ 3)$

- GB

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

• *Suitable extinguishing agents:* CO2, sand, extinguishing powder. Do not use water.

• For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Information about fire - and explosion protection:
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location. Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Not required.

- Information about storage in one common storage facult • Further information about storage conditions:
- Do not seal receptacle gas tight.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.

· Storage class: -

· 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 3)

-		that require monitoring a	t the workplace:
	outane, pure (10-20	· ·	
	t-term value: 1810 g-term value: 1450 i		
	c (if more than $0.1%$		
67-63-0 pr	opan-2-ol (2.5-5%)		
	t-term value: 1250 g-term value: 999 m		
DNELs			
Hydrocarb	oons, C9-C11, n-alk	anes, isoalkanes, cyclics,	<2% aromatics
Oral	DNEL,long term (c	hronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	hronic) - systemic effects	125 mg/kg bw/day (Consumer)
			208 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	Č (
			871 mg/m3 (Employee)
	6 Hydrocarbons, C	-	
Oral	e ,	, ,	11 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (c	chronic) - systemic effects	11 mg/kg bw/day (Consumer)
1110			25 mg/kg bw/day (Employee)
Inhalative DNEL,long term (c		nronic) - systemic effects	32 mg/m3 (Consumer) 150 mg/m3 (Employee)
67-63-0 pr	onan-2-ol		150 mg/m5 (Employee)
Oral	-	hronic) - systemic effects	26 mg/kg bw/day (Consumer)
Dermal	e ,	, ,	319 mg/kg bw/day (Consumer)
	, <u>o</u> (/ 5 55	888 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (c	hronic) - systemic effects	89 mg/m3 (Consumer)
			500 mg/m3 (Employee)
PNECs			1
67-63-0 pr	opan-2-ol		
PNEC,fres	h water	140.9 mg/l (aquatic orga	inism)
PNEC,mar	ine water	140.9 mg/l (aquatic orga	unism)
-	h water sediment	552 mg/kg (aquatic orga	
		552 mg/kg (aquatic orga	nism)
PNEC,soil		28 mg/kg (terrestrial org	ranism)
Personal p General pr Keep away Wash hand	y protection: Not re	tic measures: verages and feed. I at the end of work.	

· Material of gloves Nitrile rubber, NBR

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830



· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Safety glasses

SECTION 9: Physical	and chem	ical properties
----------------------------	----------	-----------------

General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
pH-value:	Not applicable.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 154-193 ℃
Flash point:	-97 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
Oxidising properties	No further relevant information available.
Vapour pressure at 20 °C:	8,300 hPa
Density at 20 °C:	$0.67 g/cm^3$
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).

· 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

• 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)

- GB

 Printing date 25.11.2020
 Version: 1.0
 Revision: 25.11.2020

· 10.5 Incompatible materials: No further relevant information available.

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	LD/LC50 values relevant for classification:					
<i>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics</i>						
Oral	LD50	>5,000 mg/kg (rat)				
Dermal	LD50	>5,000 mg/kg (rabbit)				
Inhalative	LC50/4 h	>5,000 mg/l (rat)				
106-97-8 b	utane, pui	'e				
Inhalative	LC50/4 h	658 mg/l (rat)				
64742-95-	6 Hydroca	rbons, C9, aromatics				
Oral	LD50	2,000-5,000 mg/kg (rat)				
Dermal	LD50	>2,000 mg/kg (rabbit)				
67-63-0 pr	opan-2-ol					
Oral	LD50	5,840 mg/kg (rat)				
Dermal	LD50	13,900 mg/kg (rabbit)				
Inhalative	LC50/6h	>25 mg/l (rat)				

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.*

• STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes: Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 6)

SECTION 13: Disposal considerations

• Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	0111750
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class Label 14.4 Packing group ADR, IMDG, IATA	2.1 2.1 None. Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litr Category A. For AEROSOLS with a capacity above 1 litr Category B. For WASTE AEROSOLS: Category C, Clear living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II Marpol and the IBC Code	of Not applicable.

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

	(Contd. of page
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
·IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 25.11.2020 Version: 1.0 Revision: 25.11.2020 (Contd. of page 8) CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - inhalation – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3