# **SAFETY DATA SHEET (SDS)**

MATERIAL NAME: CHROMA MURAL PAINT MARKERS CAMO LAST REVISION: 3/15/2021

# **SECTION 1 – IDENTIFICATION**

#### **Material Name**

CHROMA MURAL PAINT MARKERS CAMO

#### **Product Number**

Various

(Prop 65 Color. See Section 16 for additional information.)

(All information the same for all sizes.)

#### **Manufacturer Information**

Chroma Inc. 205 Bucky Drive Lititz, Pennsylvania 17543 U.S.A.

Phone: 717-626-8866; 1-800-257-8278

Fax: 717-626-9292

Email: jhirneisen@chromaonline.com; infousa@chromaonline.com

For Transportation Emergencies Only: 1-800-257-8278

For Health Emergencies Call the Poison Control Center: 1-888-516-2502

Seek medical assistance for further treatment, observation and support, if necessary.

# **SECTION 2 – HAZARDS IDENTIFICATION**

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

There are no GHS label elements.

Primary Routes of Entry: Inhalation, Ingestion, Eye, Skin

Effects and Symptoms of Acute Exposure: None Expected

Effects and Symptoms of Chronic Exposure: None Expected

OSHA: NO Carcinogen Listing: IARC: NO NTP: NO

See Section 3 for Components Affected

Medical Conditions Usually Aggravated by Over Exposure to this Product: None

# **SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

PEL/TLV Max (MG/M#) % Weight Ingredient CAS# **NTP IARC** 

NONE

All Sizes - Chroma Mural Paint Markers Camo Page 1 of 5 SDS Date 03/21

#### **SECTION 4 – FIRST AID MEASURES**

**Skin** Wash skin with soap and water or use a product specifically formulated for water based acrylic

removal. If irritation persists seek medical help.

**Eye** Check for and remove any contact lenses.

Flush eyes up to 15 minutes with water, holding eye lids open.

If irritation persists seek medical help.

**Inhalation** If person is showing adverse effects, remove person to fresh air.

Seek medical help if symptoms occur.

**Ingestion** Treat Symptomatically.

Never give anything by mouth to an unconscious person.

Seek medical help if symptoms occur.

If swallowed, call your Poison Control Center at 1-800-222-1222.

Seek medical assistance for further treatment, observation and support, if necessary.

#### Advice to Doctor:

This product carries the A.P. Seal, conforms to ASTM D4236, and is certified non-toxic by a toxicologist in association with the Art & Craft Materials Institute, Hanson, MA 02341 USA.

#### **SECTION 5 – FIRE FIGHTING MEASURES**

Flash Point (Method): N/A

Autoignition Temperature: N/A

Explosion Limits in Air (% by Volume): Not Explosive

Extinguishing Media: No Special Media Required

Fire Fighting Procedures: No Special Fire Fighting Procedures Required

Unusual Fire & Explosion Hazards: Not Combustible

# **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

#### Steps to be Taken in Case a Material is Spilled

Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section 13.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Absorb with dry earth, sand or other non-combustible material.

Small Spills: Mop up or absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

#### **Environmental Precautions**

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

#### **SECTION 7 – HANDLING & STORAGE**

# **Precautions for Safe Handling**

Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

Avoid contact with eyes. Avoid skin contact.

Observe good hygiene practices; wash hands after use.

#### **Storage Requirements**

Store at room temperature; keep from freezing.

Recommended storage conditions are between 34° F and 122° F (1° C and 50° C).

Store in original tightly closed container.

### **SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

Respiratory Protection & Special Ventilation Requirements: None needed under normal conditions of use Protective Gloves:

Eye Protection:

Other Protective Equipment:

None needed under normal conditions of use None needed under normal conditions of use None needed under normal conditions of use

Engineering Controls: None Required

# **Hygienic Work Practices**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking.

#### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point: N/A Specific Gravity (H2O=1): N/A

Vapor Pressure: N/A Melting Point: N/A

Specific Vapor Density (AIR=1): N/A Evaporation Rate: Slower than Ether Solubility in Water: N/A Reactivity in Water: Non-Reactive

Appearance & Odor: Liquid acrylic paints in assorted colors. May have slight ammonia smell.

#### **SECTION 10 – STABILITY AND REACTIVITY**

Stability (Conditions to Avoid):NoneIncompatibility (Materials to Avoid):NoneHazardous Decomposition Products:NoneHazardous Polymerization Products:None

# **SECTION 11 – TOXICOLOGICAL INFORMATION**

Acute Effects Associated with the use of this material: None Expected

The summated LD50 is 21400 mg/kg.

The summated LC50 is 41684 mg/cubic meter.

This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section 3)

#### **SECTION 12 – ECOLOGICAL INFORMATION**

### **Ecotoxicity**

The product is not classified as environmentally hazardous.

No harmful effects known other than those associated with suspended inert solids in water.

# **SECTION 13 – DISPOSAL CONSIDERATIONS**

RCRA Hazard Class (40 CFR 261): This product is not classified as hazardous waste.

# **Waste Disposal Method**

Dispose of in accordance with International, Federal, State and Local regulations.

# **SECTION 14 – TRANSPORTATION INFORMATION**

U.S. DOT (49 CFR 172.101): This product is not a hazardous material as classified by CFR 172.101.

#### **SECTION 15 – REGULATORY INFORMATION**

# **US Federal Regulations**

Contents of this SDS comply with OSHA Hazard Communications Standard 29 CFR 1910.1200 EPA SARA TITLE III Chemical Listings: None

Section 302.4 Extremely Hazardous Substances (40 CFR 355): None

Section 313 Toxic Chemicals (40 CFR 372): None

# International Regulations

#### **Canadian WHMIS:**

This product is a controlled product under Canada's Workplace Hazardous Materials Information System. It contains the following toxic or highly toxic materials:

None

# **Supplemental State Compliance Information**

# US, California, SCAQMD

Due to Southern Coast Air Quality Management District (SCAQMD) Regulations within areas of Southern California, sets may not be sold into the specified districts. Also due to SCAQMD Regulations, sales of all sizes must be tracked and reported to Chroma Inc. on a yearly basis when selling into the specified SCAQMD districts.

# US, New Jersey Right-to-Know

This product contains the following chemical(s) listed under New Jersey's Right to Know Program: Ammonia Hydroxide

#### US, Washington Children's Safe Products Act

This product contains the following chemical(s) requiring notification to the State of Washington under their Children's Safe Products Act:

None

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling: None

# **SECTION 16 – OTHER INFORMATION**

This pertains to only the color listed below, which requires the State of California Prop 65 Warning:

Camo

The VOC Content of this product is MAX 0.013 g/L.

All information the same for all colors and sizes.

This product does not contain egg, dairy, wheat, gluten, soy or peanut products, by-products or derivatives.

This product does not contain latex materials or animal derived ingredients.

# SAFETY DATA SHEET (SDS)

MATERIAL NAME: CHROMA MURAL PAINT MARKERS LAST REVISION: 2/24/2021

# **SECTION 1 – IDENTIFICATION**

**Material Name** 

CHROMA MURAL PAINT MARKERS

**Product Number** 

**Various** 

(All information the same for all colors and sizes.)

**Manufacturer Information** 

Chroma Inc. 205 Bucky Drive

Lititz, Pennsylvania 17543

U.S.A.

Phone: 717-626-8866; 1-800-257-8278

Fax: 717-626-9292

Email: jhirneisen@chromaonline.com; infousa@chromaonline.com

For Transportation Emergencies Only: 1-800-257-8278

For Health Emergencies Call the Poison Control Center: 1-888-516-2502

Seek medical assistance for further treatment, observation and support, if necessary.

#### **SECTION 2 – HAZARDS IDENTIFICATION**

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

There are no GHS label elements.

Primary Routes of Entry: Inhalation, Ingestion, Eye, Skin

Effects and Symptoms of Acute Exposure: None Expected

Effects and Symptoms of Chronic Exposure: None Expected

Carcinogen Listing: NTP: NO IARC: NO OSHA: NO

See Section 3 for Components Affected

Medical Conditions Usually Aggravated by Over Exposure to this Product: None

# **SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

PEL/TLV Max
Ingredient CAS # (MG/M#) % Weight NTP IARC

NONE

All Colors - Chroma Mural Paint Markers

Page 1 of 5

SDS Date 02/21

#### **SECTION 4 – FIRST AID MEASURES**

**Skin** Wash skin with soap and water or use a product specifically formulated for water based acrylic

removal. If irritation persists seek medical help.

**Eye** Check for and remove any contact lenses.

Flush eyes up to 15 minutes with water, holding eye lids open.

If irritation persists seek medical help.

**Inhalation** If person is showing adverse effects, remove person to fresh air.

Seek medical help if symptoms occur.

**Ingestion** Treat Symptomatically.

Never give anything by mouth to an unconscious person.

Seek medical help if symptoms occur.

If swallowed, call your Poison Control Center at 1-800-222-1222.

Seek medical assistance for further treatment, observation and support, if necessary.

#### Advice to Doctor:

This product carries the A.P. Seal, conforms to ASTM D4236, and is certified non-toxic by a toxicologist in association with the Art & Craft Materials Institute, Hanson, MA 02341 USA.

#### **SECTION 5 – FIRE FIGHTING MEASURES**

Flash Point (Method): N/A

Autoignition Temperature: N/A

Explosion Limits in Air (% by Volume): Not Explosive

Extinguishing Media: No Special Media Required

Fire Fighting Procedures: No Special Fire Fighting Procedures Required

Unusual Fire & Explosion Hazards: Not Combustible

# **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

#### Steps to be Taken in Case a Material is Spilled

Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section 13.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Absorb with dry earth, sand or other non-combustible material.

Small Spills: Mop up or absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

#### **Environmental Precautions**

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

#### **SECTION 7 – HANDLING & STORAGE**

# **Precautions for Safe Handling**

Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

Avoid contact with eyes. Avoid skin contact.

Observe good hygiene practices; wash hands after use.

#### **Storage Requirements**

Store at room temperature; keep from freezing.

Recommended storage conditions are between 34° F and 122° F (1° C and 50° C).

Store in original tightly closed container.

### **SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

Respiratory Protection & Special Ventilation Requirements: None needed under normal conditions of use Protective Gloves:

Eye Protection:

Other Protective Equipment:

None needed under normal conditions of use None needed under normal conditions of use None needed under normal conditions of use

Engineering Controls: None Required

# **Hygienic Work Practices**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking.

#### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point: N/A Specific Gravity (H2O=1): N/A

Vapor Pressure: N/A Melting Point: N/A

Specific Vapor Density (AIR=1): N/A Evaporation Rate: Slower than Ether Solubility in Water: N/A Reactivity in Water: Non-Reactive

Appearance & Odor: Liquid acrylic paints in assorted colors. May have slight ammonia smell.

#### SECTION 10 - STABILITY AND REACTIVITY

Stability (Conditions to Avoid):NoneIncompatibility (Materials to Avoid):NoneHazardous Decomposition Products:NoneHazardous Polymerization Products:None

# SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Effects Associated with the use of this material: None Expected

The summated LD50 is 21400 mg/kg.

The summated LC50 is 41684 mg/cubic meter.

This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section 3)

#### **SECTION 12 – ECOLOGICAL INFORMATION**

# **Ecotoxicity**

The product is not classified as environmentally hazardous.

No harmful effects known other than those associated with suspended inert solids in water.

# **SECTION 13 – DISPOSAL CONSIDERATIONS**

RCRA Hazard Class (40 CFR 261): This product is not classified as hazardous waste.

# **Waste Disposal Method**

Dispose of in accordance with International, Federal, State and Local regulations.

# **SECTION 14 – TRANSPORTATION INFORMATION**

U.S. DOT (49 CFR 172.101): This product is not a hazardous material as classified by CFR 172.101.

#### **SECTION 15 – REGULATORY INFORMATION**

# **US Federal Regulations**

Contents of this SDS comply with OSHA Hazard Communications Standard 29 CFR 1910.1200 EPA SARA TITLE III Chemical Listings: None

Section 302.4 Extremely Hazardous Substances (40 CFR 355): None

Section 313 Toxic Chemicals (40 CFR 372): None

# International Regulations

#### **Canadian WHMIS:**

This product is a controlled product under Canada's Workplace Hazardous Materials Information System. It contains the following toxic or highly toxic materials:

None

# **Supplemental State Compliance Information**

# US, California, SCAQMD

Due to Southern Coast Air Quality Management District (SCAQMD) Regulations within areas of Southern California, sets may not be sold into the specified districts. Also due to SCAQMD Regulations, sales of all sizes must be tracked and reported to Chroma Inc. on a yearly basis when selling into the specified SCAQMD districts.

# **US, New Jersey Right-to-Know**

This product contains the following chemical(s) listed under New Jersey's Right to Know Program: Ammonia Hydroxide

#### US, Washington Children's Safe Products Act

This product contains the following chemical(s) requiring notification to the State of Washington under their Children's Safe Products Act:

None

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling: None

# **SECTION 16 – OTHER INFORMATION**

The VOC Content of this product is MAX 0.013 g/L.

All information the same for all colors and sizes.

This product does not contain egg, dairy, wheat, gluten, soy or peanut products, by-products or derivatives.

This product does not contain latex materials or animal derived ingredients.