

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

Date of issue: 04/10/2019

Version: 1.0

SDS number: P2019032801

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Acrylic Colour Paint

1.2. Recommended use and restrictions on use

Use of the substance/mixture : painting

1.3. Supplier

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2 Causes skin irritation.
Serious eye damage/eye irritation, Category 2 Causes serious eye irritation.
Skin sensitisation, Category 1 May cause an allergic skin reaction.

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary statements (GHS US) :

Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash hands, forearms and face thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water/...
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see supplemental first aid instruction on this label)
If skin irritation occurs: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
2-Propenoic acid, homopolymer	(CAS-No.) 9003-01-4	39.8---42.3
Water	(CAS-No.) 7732-18-5	14.8---22.5
Barium sulfate	(CAS-No.) 7727-43-7	5--10
Starch, 2-hydroxypropyl ether	(CAS-No.) 9049-76-7	5
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	(CAS-No.) 25265-77-4	2
1,2-Benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5	0.2

Multicolor

Titanium dioxide	(CAS-No.) 13463-67-7	0-25
C.I. Pigment Blue 29	(CAS-No.) 57455-37-5	0-25
Iron oxide yellow	(CAS-No.) 51274-00-1	0-20
C.I. Pigment Yellow 74	(CAS-No.) 6358-31-2	0-20
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-phenyl]-	(CAS-No.) 3520-72-7	0-20
2-Naphthalenecarboxamide, 3-hydroxy-4-[(2-methyl-5-nitrophenyl)azo]-N-phenyl-	(CAS-No.) 6448-95-9	0-20
Butanamide, 2-[(4-chloro-2-nitrophenyl)azo]-N-(2-chlorophenyl)-3-oxo-	(CAS-No.) 6486-23-3	0-15
2-Naphthalenol, 1-[(2-chloro-4-nitrophenyl)azo]-	(CAS-No.) 2814-77-9	0-15
C.I. Pigment Blue 15	(CAS-No.) 147-14-8	0-15
C.I. Pigment Green 7	(CAS-No.) 1328-53-6	0-15
Diiron trioxide	(CAS-No.) 1309-37-1	0-15
Mica	(CAS-No.) 12001-26-2	0-15
Carbon black	(CAS-No.) 1333-86-4	0-10
2-Naphthalenecarboxamide, 3-hydroxy-N-(2-methylphenyl)-4-[(2,4,5-trichlorophenyl)azo]-	(CAS-No.) 6535-46-2	0-10
Quino[2,3-b]acridine-7,14-dione, 5,12-dihydro-3,10-dimethyl-	(CAS-No.) 16043-40-6	0-10
Quino[2,3-b]acridine-7,14-dione, 5,12-dihydro-	(CAS-No.) 1047-16-1	0-10
Quino[2,3-b]acridine-7,14-dione, 2,9-dichloro-5,12-dihydro-	(CAS-No.) 3089-17-6	0-10
C.I. Pigment Red 3	(CAS-No.) 2425-85-6	0-9
Fast yellow G	(CAS-No.) 2512-29-0	0-8
C.I. Pigment Violet 23	(CAS-No.) 6358-30-1	0-5
Magnetite (Fe3O4)	(CAS-No.) 1309-38-2	0-5
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[N-(4-chloro-2,5-dimethoxyphenyl)-3-oxo-	(CAS-No.) 5567-15-7	0-5

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Mechanically recover the product. On land, sweep or shovel into suitable containers. Minimise generation of dust. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Store in a well-ventilated place. Keep cool.
--------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

Barium sulfate (7727-43-7)		
ACGIH	Local name	Barium sulfate
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	Remark (ACGIH)	TLV® Basis: Pneumoconiosis
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)

Titanium dioxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)

Diiron trioxide (1309-37-1)		
ACGIH	Local name	Iron oxide
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ IRON OXIDE (FE2O3), RESPIRABLE FRACTION
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³
IDLH	US IDLH (mg/m ³)	2500 mg/m ³ (dust and fume)
NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)

Mica (12001-26-2)		
ACGIH	Local name	Mica
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (R - Respirable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: Pneumoconiosis
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (ppm)	20 mppcf
OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
IDLH	US IDLH (mg/m ³)	1500 mg/m ³ (containing <1% quartz)
NIOSH	NIOSH REL (TWA) (mg/m ³)	3 mg/m ³ (containing <1% Quartz-respirable dust)

Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
IDLH	US IDLH (mg/m ³)	1750 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Paste
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-Propenoic acid, homopolymer (9003-01-4)

LD50 oral rat	2500 mg/kg
---------------	------------

Barium sulfate (7727-43-7)

LD50 oral rat	> 15000 mg/kg
---------------	---------------

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)

LD50 oral rat	3200 mg/kg
LD50 dermal rat	> 15200 mg/kg
LC50 inhalation rat (mg/l)	> 3.55 mg/l (Exposure time: 6 h)

1,2-Benzisothiazol-3(2H)-one (2634-33-5)

LD50 oral rat	1020 mg/kg
---------------	------------

Titanium dioxide (13463-67-7)

LD50 dermal rat	> 10000 mg/kg
-----------------	---------------

3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-phenyl- (3520-72-7)

LD50 oral rat	> 5 g/kg
---------------	----------

C.I. Pigment Blue 15 (147-14-8)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

C.I. Pigment Green 7 (1328-53-6)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Carbon black (1333-86-4)

LD50 oral rat	> 15400 mg/kg
---------------	---------------

Quino[2,3-b]acridine-7,14-dione, 5,12-dihydro- (1047-16-1)

LD50 oral rat	> 7500 mg/kg
---------------	--------------

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

2-Propenoic acid, homopolymer (9003-01-4)

IARC group	3 - Not classifiable
------------	----------------------

Titanium dioxide (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

Diiron trioxide (1309-37-1)	
IARC group	3 - Not classifiable

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

C.I. Pigment Red 3 (2425-85-6)	
IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified (
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

2-Propenoic acid, homopolymer (9003-01-4)	
LC50 fish 1	580 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
LC50 fish 1	30 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

C.I. Pigment Green 7 (1328-53-6)	
LC50 fish 1	752.4 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

12.2. Persistence and degradability

Acrylic Colour Paint	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Acrylic Colour Paint	
Bioaccumulative potential	Not established.

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
Log Pow	3.47 (at 25 °C)

1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Log Pow	1.3 (at 25 °C)

C.I. Pigment Blue 15 (147-14-8)	
BCF fish 1	0.3 - 11
Log Pow	6.6 (at 25 °C)

C.I. Pigment Green 7 (1328-53-6)	
BCF fish 1	0.51 - 74

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

2-Propenoic acid, homopolymer (9003-01-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
--------------------------	-------------------------------------------------------------------------------------------------------------

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Barium sulfate (7727-43-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Starch, 2-hydroxypropyl ether (9049-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
--------------------------	-------------------------------------------------------------------------------------------------------------

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2-Benzisothiazol-3(2H)-one (2634-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

C.I. Pigment Blue 29 (57455-37-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Iron oxide yellow (51274-00-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

C.I. Pigment Yellow 74 (6358-31-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-phenyl]- (3520-72-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
2-Naphthalenecarboxamide, 3-hydroxy-4-[(2-methyl-5-nitrophenyl)azo]-N-phenyl- (6448-95-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Butanamide, 2-[(4-chloro-2-nitrophenyl)azo]-N-(2-chlorophenyl)-3-oxo- (6486-23-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
2-Naphthalenol, 1-[(2-chloro-4-nitrophenyl)azo]- (2814-77-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
C.I. Pigment Blue 15 (147-14-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
C.I. Pigment Green 7 (1328-53-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Diiron trioxide (1309-37-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Carbon black (1333-86-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
2-Naphthalenecarboxamide, 3-hydroxy-N-(2-methylphenyl)-4-[(2,4,5-trichlorophenyl)azo]- (6535-46-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quino[2,3-b]acridine-7,14-dione, 5,12-dihydro- (1047-16-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quino[2,3-b]acridine-7,14-dione, 2,9-dichloro-5,12-dihydro- (3089-17-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
C.I. Pigment Red 3 (2425-85-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Fast yellow G (2512-29-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
C.I. Pigment Violet 23 (6358-30-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Magnetite (Fe3O4) (1309-38-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[N-(4-chloro-2,5-dimethoxyphenyl)-3-oxo- (5567-15-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Titanium dioxide (13463-67-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Carbon black (1333-86-4)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Acrylic Colour Paint

Safety Data Sheet

according to OSHA HazCom Standard (2012)

Component	State or local regulations
2-Naphthalenol, 1-[(2-chloro-4-nitrophenyl)azo]- (2814-77-9)	U.S. - Maine - Chemicals of Concern
Carbon black (1333-86-4)	U.S. - Maine - Chemicals of Concern
C.I. Pigment Red 3(2425-85-6)	U.S. - Maine - Chemicals of Concern

SECTION 16: Other information

Abbreviations and acronyms:

EC50	Median effective concentration
BCF	Bioconcentration factor
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
NOAEL	No-Observed Adverse Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.