

Product information | TECHNICAL DATA SHEET

WATER BASED VARNISH. Water soluble, odorless, matt and gloss finish and for indoor use.
300 ml

GENERAL DESCRIPTION

Water based acrylic varnish spray paint that is quick-drying, with excellent characteristics that offer high quality finishes, durability, on multiple surfaces without yellowing.

FEATURES

- Water based product.
- Acrylic.
- Cures well.
- Non-yellowing.
- Sticks well to the majority of surfaces.
- Easy to apply.

INSTRUCTIONS FOR USE

- Properly shake the aerosol before using for at least one minute after the agitator ball is freed.
- Use on clean and dry surfaces. Remove rust with a wire brush. For use on plastics and polyester, prime with a suitable adhesion promoter. Due to the multitude of materials and methods of application, it is recommended to test the product on an inconspicuous area first.
- Apply thin coats for best results. Three layers are better than one thick layer. The number of layers applied may affect the level of glossiness
- Do not apply to plugged-in equipment and use the product in well ventilated areas.
- Ask for safety data sheets.

PHYSICAL PROPERTIES

Bonding agent:	Acrylic
Color:	Transparent
Gloss 60° (ASTM D-1640 ISO 1517):	gloss >90%, matt <10%
Touch Drying (ASTM D-1640 ISO 1517):	30'
Total Drying (ASTM D-1640 ISO 1517):	12 h
Theoretical yield (continuous painting):	2m ² for 300 ml
Thinner:	Water and alcohol
Shelf life:	(Well Stored) 5 Years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity 85% R.H.P
Heat painting resistance:	Undetermined

FINISHES 2 varnishes

Barniz Mate / Matte Varnish EX019W0907	☼☼☼	▬▬▬▬▬▬▬▬▬▬
Barniz Brillante / Glossy Varnish EX019W0900	☼☼☼	▬▬▬▬▬▬▬▬▬▬



APPLICATIONS

The product can be used on many surfaces: iron, steel, wood, directly on expanded polystyrene.

- Fine Art
- Graffiti
- DIY
- Manualidades
- Industry
- Crafts

Due to its low odor and due to its content of water-based resins, it is the ideal product for interior use and in spaces with poor ventilation.

APPEARANCE



LABEL



CAP SYSTEM



PACKAGING

Nominal capacity: 300 ml.
Head resistance of packaging: <50°C
Propellant: DME
VOC's (g/l): 525-460*

Box (4 units)
140 X 140 X 160 mm.

